

Dynamic fragmentation using phase-field modeling of fracture

S. Durussel^{1*}, G. Anciaux¹, L. De Lorenzis² J.-F. Molinari¹

¹ Civil Engineering Institute, Institute of Materials Science and Engineering, École Polytechnique Fédérale de Lausanne (EPFL), Station 18, 1015 Lausanne, Switzerland, shad.durussel@epfl.ch

² Department of Mechanical and Process Engineering, ETH Zürich, Zürich, 8092, Switzerland

Dynamic fragmentation is a process during which a material or structure subjected to intense loads fails catastrophically through the initiation, propagation and coalescence of a multitude of cracks. It is a key topic in many fields of engineering, as for instance in aerospace industry, where the impact of space debris with satellites is of great concern. Robust numerical models are direly needed to develop a fundamental understanding of such events, in particular to be able to predict the statistical distributions of fragment sizes, shapes and velocities resulting from such a collision.

A well established way to address this problem is to use FE solid mechanics models coupled with cohesive elements [1]. Cohesive cracks give an explicit representation of crack surfaces and simplify the treatment of contacts between fragments, a crucial factor to predict debris velocities. However, the cohesive approach is known to suffer from mesh dependency, with crack paths that depend on the underlying mesh, resulting in non-robust predictions of fragments shapes.

Phase-field modeling of fracture belongs to another family of methods using diffuse crack approaches and, as opposed to cohesive models, where the fracture paths are not dependent on the underlying mesh. Phase-field has been shown to lead to promising results in many problems, not only in quasi-static but also in dynamics where different mechanisms such as branching can be observed [2]. In addition, the multiplicity of possible crack patterns obtained with phase-field for a single loading case in quasi-static has been discussed in [3] where different simulation outcomes can be associated with probabilities. This study is yet to be extended to dynamic cases where the evolution of statistics on fracture paths with the loading rate can be explored. This stochastic approach is of great interest in the context of dynamic fragmentation to enrich statistical data of fragment sizes and shapes in light of material heterogeneity.

The phase-field approach to fracture, addressing the issue of mesh-dependency, will be examined in fragmentation dynamics and numerical data shall be compared to outcomes of cohesive crack models. Then, adaptations of fragment tracking algorithms to diffuse crack approaches will be discussed. Finally, the sensitivity of debris distributions to small variations in the material parameters or the geometry of the model will be analyzed.

References

- [1] M. Vocialta, N. Richart, J.-F. Molinari, 3D dynamic fragmentation with parallel dynamic insertion of cohesive elements, *International Journal for Numerical Methods in Engineering*, 109, (2017), 1655-1678.
- [2] J. Bleyer, C. Roux-Langlois, J.-F. Molinari, Dynamic crack propagation with a variational phase-field model: limiting speed, crack branching and velocity-toughening mechanisms, *International Journal of Fracture*, 204, (2017), 79–100.
- [3] T. Gerasimov, U. Römer, J. Vondřejc, H. G. Matthies, L. De Lorenzis, Stochastic phase-field modeling of brittle fracture: Computing multiple crack patterns and their probabilities, *Computer Methods in Applied Mechanics and Engineering*, 372, (2020), 113353.